

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
26 February 2004 (26.02.2004)

PCT

(10) International Publication Number
WO 2004/017183 A2

(51) International Patent Classification⁷: **G06F 1/00**

[GB/GB]; Star Internet, Brighthouse Court, Barmwood,
Gloucester GL4 3RT (GB).

(21) International Application Number:

PCT/GB2003/003476

(74) Agents: **AYERS, Martyn, Lewis, Stanley et al.**; J.A.
Kemp and Co., 14 South Square, Gray's Inn, London
WC1R 5JJ (GB).

(22) International Filing Date: 11 August 2003 (11.08.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

0218993.4

14 August 2002 (14.08.2002) GB

(71) Applicant (for all designated States except US): **MES-SAGELABS LIMITED** [GB/GB]; 1270 Landsdowne
Court, Gloucester Business Park, Gloucester GL3 4AB
(GB).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,

(72) Inventor; and

(75) Inventor/Applicant (for US only): **SHIPP, Alexander**

[Continued on next page]

(54) Title: METHOD OF, AND SYSTEM FOR, HEURISTICALLY DETECTING VIRUSES IN EXECUTABLE CODE



(57) Abstract: A method of, and system for, virus detection has a database of known patterns of start-up code for executable images created using a collection of known compilers and uses examination of the start-up code of the image by reference to this database to determine whether or not the executable image is likely to have been subject to infection by viral code. In particular, the system seeks to determine whether the expected flow and execution of the image during start up has had viral code interjected into it. Various heuristics to assist in assessing the likely presence of viral code are disclosed.



SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *without international search report and to be republished upon receipt of that report*

METHOD OF, AND SYSTEM FOR, HEURISTICALLY DETECTING VIRUSES IN EXECUTABLE CODE

The present invention relates to a method of, and system for, heuristically
5 detecting viruses in executable code by searching the code for known startup sequences.

A common form of computer virus infection is where the virus's executable
code is attached to, or embedded in, a program or other computer file containing executable
code which appears, on the face of it, to be benign. One well-established method of virus
propagation is where the virus, once activated on a host machine such as a user's PC, will
10 attach itself to one or more programs found on the host in such a way that that program, once
run, will execute the virus's code giving it the opportunity to propagate again and/or to
undertake whatever other malignant behaviours (such as destruction of files, etc.) have been
programmed into it. This method of propagation does, of course, provide an opportunity to
detect the virus, for example by associating checksums with program files and detecting when
15 this checksum changes. That is of course only one of the many strategies which have been
devised to detect viruses.

Another well-known method of detecting viruses, implemented in many of the
anti-virus software packages which are available, involves scanning program and other files
for certain characteristic sequences of bytes (known as signatures) which indicate the likely
20 presence of a virus. One of the practical problems with signature-based detection is that it
requires some skill and a significant amount of time, when a new virus is first detected, to
establish a suitable characteristic signature of it. This signature needs to be one which does
not produce too many false positives and which does not misidentify the virus, for example as
an existing one with a more benign payload. This signature information then needs to be
25 disseminated to sites which use the anti-virus package in question before it can be used there
to detect the newly-identified virus. In recent years, many of the notable virus outbreaks have

involved viruses which propagate over the internet and it takes time for publishers of anti-virus software to react when a virus outbreak occurs.

Some internet service providers offer anti-virus scanning of internet traffic passing through their internet nodes as a value-added service.

5 The present invention relates to a method of virus detection which is intended to be useful for ISPs performing anti-virus scanning, e.g. of executables such as program files attached to emails, though it is by no means limited to that application and may be used in any anti-virus package.

 According to the present invention there is provided a method of detecting
10 virus infection of an executable image comprising:

 identifying by reference to a database of known executable image layouts, the layouts to which the executable image conforms;

 identifying start-up code within the executable image by reference to the identified image layout; and

15 examining the start-up code with reference to a database of start-up code characteristics to determine whether the image is likely to have been subject to viral modification.

 The invention also provides a system for detecting virus infection of an executable image comprising:

20 means for identifying, by reference to a database of known executable image layouts, to which one of those layouts the executable image conforms;

 means for identifying start-up code within the executable image by reference to the identified image layout; and

means for examining the start-up code with reference to a database of start-up code characteristics to determine whether the image is likely to have been subject to viral modification.

The invention will be further described by way of non-limiting example with
5 reference to the accompanying drawings, in which:-

Figures 1a and 1b show an example of a virus changing the program entry point;

Figures 2a and 2b show an example of a virus overwriting code at the program entry point; and

10 Figure 3 shows a system according to the present invention.

Before proceeding with the description of the illustrated embodiment of the invention, some terms will be explained.

MD5 (message digest 5) checksum. MD5 is a one-way hashing algorithm – it generates a large number (the MD5 checksum) after analysing a byte stream – such as a file.

15 The chances of two files generating the same large number are very small. It is also very difficult to create a file which will generate any particular MD5 checksum.

False positive: A false positive occurs when an anti-virus product identifies a particular file as being malware, whereas in fact it is not.

Regular expression: Regular expressions are strings which can be used to
20 express patterns for pattern matching purposes. For instance, the perl regular expression

`/^hello [0-9]+/`

matches any string starting with the letters 'hello', then a space, then one or more digits. Some languages such as perl have native support for regular expressions; for others, libraries are available which implement regular expression matching.

Compiler: According to strict usage, a compiler generates one or more object modules from program source code. These object modules are typically not executable programs per se but require an additional step of linking by a linker. The action of a linker is typically to generate an image of an executable by linking together the object module(s), and external binary libraries which the module(s) reference; the production of the image may involve the pre-pending of a header region according to an executable file layout of a target operating system as well as the addition of resources such as bitmaps and the like. The term “compiler” as used herein is intended to include a linker, if required from a technical standpoint. What the compiler produces is not necessarily a stand-alone program, of course: compilers also produce executables such as dynamic link libraries and device drivers.

Program image: A program image is a sequence of bytes of executable code, which may exist on disk, in memory or in a network socket stream. In its on-disk form the image may be part of a program file which also includes a program header containing the information normally found in such programs.

To gain control, a virus must insert itself into the execution path of program code. Although, theoretically, the virus can insert itself anywhere in a program, if it inserts itself into the middle then this lessens the chance of it gaining control, since the place it inserts itself into may be executed rarely or never. Therefore, many viruses replace the startup code of programs with their own startup code. This guarantees they will be executed, giving them a better chance of survival. The on-disk image of an executable program must conform to a layout appropriate to the operating system and any given operating system may support a number of said layouts. At the time of writing the majority of Microsoft Windows™ programs conform to the “Windows PE” layout. These layouts, as exemplified in Figure 1, usually begin with a header containing e.g. checksum and relocation tables for segment fix-ups which are carried out by the operating system’s (OS) loader as it loads the program. At

some point the OS will hand over control to the program by a call to the program's entry point, which is indicated in the program header.

What happens after that depends on the nature of the program and on the compiler and linker which have been used to create it. Fully compiled, user-runnable,

5 programs generally have a runtime library link which handles a number of common tasks. In particular, the runtime library usually contains routines which are involved at start-up and perform tasks such as setting up in-memory structures such as the program stack and heap. The program code written by the program's author generally assumes that these actions will have been performed by start-up code in the runtime library before the author's code begins to
10 execute. All this is not to say that for a given compiler and linker and runtime library, the start-up code of a program created using them will be completely invariant, but rather that different programs compiled with the same compiler and linker and runtime library exhibit sufficient similarity, at least in terms of code found via the program entry point, to provide the basis for determining whether viral code has been patched into the program after it was
15 compiled and linked.

To gain control at startup, a virus can change the program start point to point to the virus start code, or it can change part of the actual startup code, replacing it with a jump or call to its own code. Figure 1 shows an example of a virus changing the program start point to point to its own code. Figure 2 shows an example of a virus changing the startup code,
20 replacing it with a jump to its own code.

As mentioned above, often a particular compiler and set of libraries will generate the same startup code for all, or a large proportion of programs it generates. Sometimes, this is because it starts with a standard library sequence that performs common tasks necessary during startup. Sometimes this is because the compiler generates applications
25 in a particular way (eg Visual BASIC).

If it can be identified that a particular program contains the common startup code, but that the program does not actually start with this code, then this is very suspicious, and the program can be flagged as potentially containing a virus. This would be the case with the example in Figure 1.

5 If it can be identified that a particular program starts with code similar to the common startup code, but that the beginning of this code has been changed, then this is very suspicious, and the program can be flagged as potentially containing a virus. This would be the case with the example in Figure 2.

10 The operation of the present embodiment proceeds by examination of an image of a program, be it on disk, in memory, or part of a network packet stream, with reference to a database of characteristics of programs created using known compilers and a pattern matcher to determine whether the program image, in particular the start-up code deviates from what would be expected from that compiler in a way which makes the program suspicious.

15 Figure 3 shows one embodiment of the invention. For the purposes of illustration, it may be assumed that files to be scanned are delivered from an input queue and each one is processed by the system 10 shown in Figure 3.

20 1) By analysing the suspicious image using a file-type analyser 20, the type can be determined. For instance, it may be non-program, or program. Non-programs are not analysed further. Programs are further classified depending on their type – for instance, DOS, Windows PE, Windows NE, Linux ELF, Macintosh, etc. This analysis is done by file-type analyser 20. Note that in the case of a file image, the file type (e.g. .EXE, .DLL, etc.) should be disregarded.

25 2) Depending on the type of program, this can then be searched by start up code search 30 for appropriate start-up code against a database of start-up code sequences. For instance, Windows PE files may be searched for startup code created by the Microsoft Visual

Studio C compiler, Borland C compilers, the Microsoft Visual BASIC compiler and the Delphi compiler.

3) If the startup code search 30 determines that start-up code is found, but the program does not actually start with this code, then it hands to the suspicious file handler
5 (step 6).

4) If entry point code analyser 40 determines that the program starts with code similar to known startup code, then go to the exception list step (6) which is handled by the suspicious file handler 60.

5) If execution arrives at the exit point 70 the program is flagged 'not
10 suspicious' and no further action is taken.

6) The suspicious file handler 60 may make use of an exception list to prevent false positives. For instance, there may be genuine program files which appear to contain startup code, but do not, programs which contain recognised startup code but not at the entry point and programs which for some reason contain the startup code but start with
15 some other code. These genuine files can be included in the exception list. The exception list can work in various ways, including but not limited to comparing the MD5 checksum of a file with a list of known checksums, or by searching the files for regular expressions, or by comparing the actual startup code with a list of known exception startup codes. If any exception list match occurs, no further action is taken.

20 A further consideration for which the suspicious file handler may be programmed to take account is that utility programs exist which "repackage" program files in certain ways. One such type of utility is the compression utility exemplified by Blinker (www.blink.com) which compresses an executable and adds a stub loader so that when the program is run, the stub loader is invoked and decompresses the executable's image. In most
25 cases, the compression utility will compress the original executable's startup code which will

not therefore be found by pattern matching for startup code. However, supposing for some reason a particular startup code sequence was uncompressible, and therefore remained unaltered. This could then generate a false positive. To avoid this, an exception list entry could be created which would, in effect, say "Ignore all programs packed by Blinker". There are various ways to do this for the different utilities which exist, including detecting the startup code of their own which they insert in the executable image and also checking the section characteristics (such as name, sequence, flags) in layouts such as a PE file.

7) Otherwise, the program is flagged as possibly containing a virus. This may be used as an absolute decision, or combined with other heuristics to make an overall decision as to whether the program is viral or not.

Programs which are stopped as viral, but which do not turn out to be viral, can be analysed, and an exception list entry generated, so that similar false positives do not occur in future.

As well as using this as a stand-alone virus detection algorithm, this can be combined with other techniques as part of a larger system. For instance, programs flagged as viral by this method may be allocated a certain score, or variety of scores depending on the exact circumstances. Scores may also be assigned using other heuristic techniques, and only if the total score passes some limit is the program flagged as viral.

Once flagged as viral, any suitable remedial action may be taken, either by the system acting autonomously e.g. by moving the program file to a quarantine directory, or by signalling a human operator that intervention is required.

Example of examining a suspicious file

Following is a simplistic example of an algorithm for determining if a file is likely to be a Windows PE file, which may be implemented by the file type analyser.

Read in first 2 bytes. If these are not 'MZ' then stop
 Read in another 58 bytes.
 Read in 4 bytes into variable x (treating using intel byte-ordering)
 Seek to offset x in file
 Read in 4 bytes
 If bytes are P E \0 \0, then file is likely to be a Windows PE file

5

Example of searching file for known startup code

The following is a common startup sequence for programs generated for the

10 Microsoft Development Studio C compiler for the windows environment.

	Hex bytes in file	Human-readable disassembly
	55	push ebp
	8B EC	mov ebp, esp
15	6A FF	push 0FFFFFFFh
	68 10 11 00 01	push offset var1
	68 80 22 00 01	push offset loc_1002280
	64 A1 00 00 00 00	mov eax, large fs:0
	50	push eax
20	64 89 25 00 00 00 00	mov large fs:0, esp
	83 C4 E0	add esp, 0FFFFFFE0h
	53	push ebx
	56	push esi
	57	push edi
25	89 65 E8	mov [ebp+var_18], esp
	C7 45 FC 00 00 00 00	mov [ebp+var_4], 0
	6A 01	push 1
	FF 15 40 10 00 01	call ds:__set_app_type
	83 C4 04	add esp, 4
30	C7 05 B0 32 00 01 FF FF FF FF	mov dword_10032B0, 0FFFFFFFh
	C7 05 B4 32 00 01 FF FF FF FF	mov dword_10032B4, 0FFFFFFFh
	FF 15 4C 10 00 01	call ds:__p_fmode
	8B 0D D0 30 00 01	mov ecx, dword_10030D0
	89 08	mov [eax], ecx
35	FF 15 68 10 00 01	call ds:__p_commode
	8B 15 CC 30 00 01	mov edx, dword_10030CC
	89 10	mov [eax], edx
	A1 64 10 00 01	mov eax, ds:_adjust_fdiv
	8B 08	mov ecx, [eax]
40	89 0D B8 32 00 01	mov dword_10032B8, ecx
	E8 16 01 00 00	call unknown_libname_2
	A1 AC 30 00 01	mov eax, dword_10030AC
	85 C0	test eax, eax
	75 0E	jnz short loc_1002171
45	68 60 22 00 01	push offset unknown_libname_1
	FF 15 60 10 00 01	call ds:_setusermatherr
	83 C4 04	add esp, 4
	E8 CA 00 00 00	call _setdefaultprecision
	68 0C 30 00 01	push offset unk_100300C
50	68 08 30 00 01	push offset unk_1003008
	E8 B1 00 00 00	call _initterm
	83 C4 08	add esp, 8
	8B 15 C8 30 00 01	mov edx, dword_10030C8
	89 55 D8	mov [ebp+var_28], edx

	8D 45 D8	lea	eax, [ebp+var_28]
	50	push	eax
	8B 0D C4 30 00 01	mov	ecx, dword_10030C4
	51	push	ecx
5	8D 55 E0	lea	edx, [ebp+envp]
	52	push	edx
	8D 45 D4	lea	eax, [ebp+argv]
	50	push	eax
	8D 4D E4	lea	ecx, [ebp+argc]
10	51	push	ecx
	FF 15 58 10 00 01	call	ds: __getmainargs
	83 C4 14	add	esp, 14h
	68 04 30 00 01	push	offset unk_1003004
	68 00 30 00 01	push	offset unk_1003000
15	E8 76 00 00 00	call	_initterm
	83 C4 08	add	esp, 8
	FF 15 30 10 00 01	call	ds: __p__initenv
	8B 55 E0	mov	edx, [ebp+envp]
	89 10	mov	[eax], edx
20	8B 45 E0	mov	eax, [ebp+envp]
	50	push	eax
	8B 4D D4	mov	ecx, [ebp+argv]
	51	push	ecx
	8B 55 E4	mov	edx, [ebp+argc]
25	52	push	edx
	E8 40 F5 FF FF	call	_main
	83 C4 0C	add	esp, 0Ch
	89 45 DC	mov	[ebp+var_24], eax
	50	push	eax
30	FF 15 48 10 00 01	call	ds: exit
	EB 22	jmp	short loc_1002210
	8B 45 EC	mov	eax, [ebp-14h]
	8B 08	mov	ecx, [eax]
	8B 09	mov	ecx, [ecx]
35	89 4D D0	mov	[ebp-30h], ecx
	50	push	eax
	51	push	ecx
	E8 31 00 00 00	call	_XcptFilter
40	83 C4 08	add	esp, 8

	C3	retn
	8B 65 E8	mov esp, [ebp-18h]
	8B 55 D0	mov edx, [ebp-30h]
	52	push edx
5	FF 15 50 10 00 01	call ds:_exit
	83 C4 04	add esp, 4
	C7 45 FC FF FF FF FF	mov [ebp+var_4], 0FFFFFFFFh
	8B 4D F0	mov ecx, [ebp+var_10]
	64 89 0D 00 00 00 00	mov large fs:0, ecx
10	5F	pop edi
	5E	pop esi
	5B	pop ebx
	8B E5	mov esp, ebp
	5D	pop ebp
15	C3	retn

However, we cannot simply search for this particular byte pattern (55, 8B, EC, 6A, FF, 68, 10, 11, 00, 01, etc); many of the values are offsets to other routines or data structures, which will vary from program to program because they will be located in different places, and therefore have different offsets. For instance, the fourth instruction, push offset var1, has the byte sequence 68 10 11 00 01 in the example, because the variable var1 is located at offset 0x01001110 in this program. In another program, var1 may be located at a different offset (say 0x10011EF), and the fourth instruction will then have the byte sequence 60 EF 11 00 01.

A simplistic search could therefore match those bytes that are constant, and skip over the bytes that vary. For every byte in the program file, we attempt to see if the search pattern fits, and if it does we have found the code. If it does not, we carry on with the next byte in the file and so on until the end of the file is reached.

	Match 1 byte: 55
30	Match 2 bytes: 8B, EC
	Match 2 bytes: 6A, FF
	Match 1 byte: 68
	Skip the next 4 bytes
	Match one byte: 68
35	Skip the next 4 bytes
	...and so on until
	Match 2 bytes 8B, E5
	Match 1 byte 5D
40	Match 1 byte C3

A more detailed search could perform other checks on the bytes that vary. For instance, if the bytes are known from knowledge of the start-up code which the compiler generates to be an offset to a data structure containing a value such as 'Press any key to continue', the search could check that this offset actually contains this data. If they are an
 5 offset to a known routine, the search could recursively check that the known routine matches a correct pattern.

For instance, suppose that in the original pattern, that var1 contains the string 'hello'. The search algorithm might now be:

10 Match 1 byte: 55
 Match 2 bytes: 8B, EC
 Match 2 bytes: 6A, FF
 Match 1 byte: 68
 Read the next 4 bytes into variable offsetcheck1
 Match one byte: 68
 15 Skip the next 4 bytes
 ...and so on until
 Match 2 bytes 8B, E5
 Match 1 byte 5D
 20 Match 1 byte C3
 Then:
 Move to the location held in offsetcheck1 (in our example, this would be 0x01001110).
 25 Match the next 5 bytes: 'hello'
 If we find this startup code pattern, we then check if it is located at the entry point of the program. If it is, then all is OK. If not, then this is flagged as suspect (startup code found, but program does not start with this code).

Example of searching file for changed startup code

30 Using the same example startup code as before, we could use the following algorithm to determine if the file contained changed startup code:

Go to offset of program start.
 Skip 15 bytes
 Match 6 bytes: 64, A1, 00, 00, 00, 00
 35 Match 1 byte: 50
 Match 7 bytes: 64 89 25 00 00 00 00

...and so on until
Match 2 bytes 8B, E5
Match 1 byte 5D
Match 1 byte C3

5

If code did not match, stop search.

10 If code does match, then the bytes from offset 15 onwards are part of a known startup sequence. If the first 15 bytes also match this startup sequence, all is OK. Otherwise this is potentially interesting. The checks therefore continue as follows.

Go to offset program start
Match 1 byte: 55
Match 2 bytes: 8B, EC
Match 2 bytes: 6A, FF
Match 1 byte: 68
Skip the next 4 bytes
Match one byte: 68
Skip the next 4 bytes

15

20

If all matches succeeded, then this is part of a known startup sequence.

Otherwise, this is flagged as 'changed startup code'.

CLAIMS

1. A method of detecting virus infection of an executable image comprising:
identifying by reference to a database of known executable image layouts, the
layouts to which the executable image conforms;

5 identifying start-up code within the executable image by reference to the
identified image layout; and

examining the start-up code with reference to a database of start-up code
characteristics to determine whether the image is likely to have been subject to viral
modification.

10

2. A method according to claim 1, wherein the database of start-up code
characteristics includes patterns characteristic of start-up code generated by a set of known
compilers.

15 3. A method according to claim 2 for scanning the executable image for patterns
of start-up code expected to be present as a consequence of that compiler having been used to
create the executable image and determining, in regard to patterns so found, whether there is
evidence of viral code interposed in the execution path from the entry point of the executable
image.

20

4. A method according to claim 3 wherein, if it is determined that the executable
image contains known start-up code but that execution of the image will not actually start
with that code, flagging the image as suspicious from the point of view of possibly containing
viral code.

5. A method according to claim 3 or 4 wherein, if it is determined that the executable image starts with code similar to the known start-up code but the beginning of this code has been changed, flagging the image as suspicious from the point of view of possibly containing viral code.

5

6. A method according to any one of the preceding claims wherein the start up code database includes records of data values associated with routines which form part of the start up code and including the step of identifying the data in the executable image corresponding to at least one such data value and comparing it with that value.

10

7. A system for detecting virus infection of an executable image comprising:
means for identifying, by reference to a database of known executable image layouts, to which one of those layouts the executable image conforms;
means for identifying start-up code within the executable image by reference to
15 the identified image layout; and
means for examining the start-up code with reference to a database of start-up code characteristics to determine whether the image is likely to have been subject to viral modification.

20

8. A system according to claim 7, wherein the database of start-up code characteristics includes patterns characteristic of start-up code generated by a set of known compilers.

25

9. A system according to claim 8 for scanning the executable image for patterns of known startup code and determining, in regard to patterns so found, whether there is

evidence of viral code interposed in the execution path from the entry point of the executable image.

10. A system according to claim 9 wherein, if it is determined that the executable

5 image contains known start-up code but that execution of the image will not actually start with that code, flagging the image as suspicious from the point of view of possibly containing viral code.

11. A system according to claim 9 or 10 wherein, if it is determined that the

10 executable image starts with code similar to the expected start-up code but the beginning of this code has been changed, flagging the image as suspicious from the point of view of possibly containing viral code.

12. A system according to any one of claims 7-11 wherein the start up code

15 database includes records of data values associated with routines which form part of the start up code and including means for identifying the data in the executable image corresponding to at least one such data value and comparing it with that value.

13. A method of detecting virus infection of an executable image substantially as

20 hereinbefore described and with reference to the accompanying drawings.

14. A system for of detecting virus infection of an executable image substantially

as hereinbefore described and with reference to the accompanying drawings.

1/3

Fig.1a.

EXAMPLE OF VIRUS
CHANGING PROGRAM
ENTRY POINT




Fig.1b.

EXAMPLE OF VIRUS
CHANGING PROGRAM
ENTRY POINT




Fig.2a.

EXAMPLE OF VIRUS
OVERWRITING CODE AT
PROGRAM ENTRY POINT






Fig.2b.

EXAMPLE OF VIRUS
OVERWRITING CODE AT
PROGRAM ENTRY POINT



3/3

Fig.3.



(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
26 February 2004 (26.02.2004)


PCT

(10) International Publication Number
WO 2004/017183 A3

- (51) International Patent Classification⁷: **G06F 1/00** [GB/GB]; Star Internet, Brighthouse Court, Barnwood, Gloucester GL4 3RT (GB).
- (21) International Application Number: PCT/GB2003/003476
- (22) International Filing Date: 11 August 2003 (11.08.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 0218993.4 14 August 2002 (14.08.2002) GB
- (71) Applicant (for all designated States except US): MES-SAGELABS LIMITED [GB/GB]; 1270 Landsdowne Court, Gloucester Business Park, Gloucester GL3 4AB (GB).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): SHIPP, Alexander
- (74) Agents: AYERS, Martyn, Lewis, Stanley et al.; J.A. Kemp and Co., 14 South Square, Gray's Inn, London WC1R 5JJ (GB).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,

[Continued on next page]

(54) Title: METHOD OF, AND SYSTEM FOR, HEURISTICALLY DETECTING VIRUSES IN EXECUTABLE CODE



(57) Abstract: A method of, and system for, virus detection has a database of known patterns of start-up code for executable images created using a collection of known compilers and uses examination of the start-up code of the image by reference to this database to determine whether or not the executable image is likely to have been subject to infection by viral code. In particular, the system seeks to determine whether the expected flow and execution of the image during start up has had viral code interjected into it. Various heuristics to assist in assessing the likely presence of viral code are disclosed.

WO 2004/017183 A3



SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- *with international search report*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

(88) Date of publication of the international search report:

3 June 2004

INTERNATIONAL SEARCH REPORT

PCT/GB 03/03476

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 G06F1/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G06F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, INSPEC

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	NACHENBERG C S: "A NEW TECHNIQUE FOR DETECTING POLYMORPHIC COMPUTER VIRUSES. A THESIS SUBMITTED IN PARTIAL SATISFACTION OF THE REQUIREMENTS FOR THE DEGREE MASTER OF SCIENCE IN COMPUTER SCIENCE AND ENGINEERING" THESIS UNIVERSITY OF CALIFORNIA, XX, XX, 1995, pages I-V, 1-127, XP000197628 section 3.1-3.2 section 6.2.1 page 17; figure 2.2 -----	1, 13, 14

☐ Further documents are listed in the continuation of box C.

☐ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- *Z* document member of the same patent family

Date of the actual completion of the international search

8 April 2004

Date of mailing of the international search report

16/04/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Fleckinger, C